

Fluke 374 FC True-RMS AC/DC Clamp Meter

This clamp meter offers advanced troubleshooting performance and is now part of the Fluke Connect family of wireless test tools.

DESCRIPTION:

The Fluke 374 FC is part of the Fluke Connect family of wireless test tools. Now you can:

- Trend measurements and pinpoint intermittent faults by connecting your meter to your phone via Fluke Connect® Measurements app
- Transmit results wirelessly via Fluke Connect® Measurements app
- Create and send reports right from the field
- Stay safely away from the arc flash zone through Bluetooth connectivity to Apple and Android devices
- Proprietary inrush measurement technology to filter out noise and capture motor starting current exactly as the circuit protection sees it
- Ergonomic design fits in your hand and can be used while wearing personal protective equipment
- Large, easy to read backlight display automatically sets the correct measurement range so you do not need to change the switch positions while taking a measurement



SPECIFICATIONS:

Fluke 374 FC Clamp Meter Specifications:

- | | |
|------------------------------------|---|
| • Diameter of measurable conductor | 01.3" or 34 mm max |
| • Operating temperature | -14 to 122°F (-10 to 50°C) |
| • Storage Temperature | -40 to 140°F (-40 to 60°C) |
| • Operating Humidity | < 90% @ 10 to 30°C, < 75% @ 30 to 40°C |
| • Operating Altitude | 0 to 3000 m |
| • Size | 246 x 83 x 43 mm, (9.685 x 3.267 x 1.692 in.) |
| • Weight | 388g, (14 oz.) |
| • Temperature Coefficient | 0.01% °C
(<18°C or > 28°C) |

INCLUDED:

- Soft carrying case
- TL75 test leads
- Two AA Alkaline batteries
- Coated instruction card
- Safety information sheet

